(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 27 May 2004 (27.05.2004)

(10) International Publication Number WO 2004/044096 A1

(51) International Patent Classification7:

C10G 27/04

(21) International Application Number:

PCT/GB2003/004648

- (22) International Filing Date: 30 October 2003 (30.10.2003)
- (25) Filing Language:

(26) Publication Language:

English

- (30) Priority Data: 11 Novembe) 2002 (11.11.2002) 0226178.2 GB
- (71) Applicant (for all designated States except US): JOHN-SON MATTHEY PLC [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): ABBOTT, Peter, Edward, James [GB/GB]; Glebe House, Muirfield Road, Eaglescliffe, Cleveland TS16 9EJ (GB).
- (74) Agents: GIBSON, Sara, Hillary, Margaret et al.; Intellectual Property Department, Johnson Matthey Catalysts, P.O. Box 1 Belasis Avenue, Billingham, Cleveland TS23 1LB (GB).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DESULPHURISATION

(57) Abstract: Propane and/or butanes are separated from a hydrocarbon feedstock contaminated with alkyl mercaptans by fractional distillation at such a pressure that the separated overheads stream containing said propane and/or butanes is at a temperature in the range 50 to 100°C. Sufficient oxygen is introduced into the hydrocarbon feedstock to oxidise the mercaptans therein and the resultant mixture is subjected to the fractional distillation in a column including at least one bed of a catalyst capable, under the prevailing conditions, of oxidising the mercaptans to higher boiling point sulphur compounds. These higher boiling point sulphur compounds are separated as part of the liquid phase from the distillation.